

## Esotec System 342

The Esotec System 342 three-way component system includes one pair each of the MD 102 soft-dome tweeter, MD 142 soft-dome midrange, MW 162 mid/woofer and X 362 audiophile quality, competition-grade, adjustable passive crossover networks into an ultra high performance package that delivers Dynaudio's advanced high fidelity sound and an incredible level of installation flexibility. All mounting hardware and grilles are included.

Taking the performance of the company's two-way systems one step further, Dynaudio's Esotec three-way systems incorporate the innovative MD 142 soft-dome midrange unit that adds a further sense of refinement to the system while offering such at the highest possible value.



- Esotec System 342**
- Three-Way System
  - 7" MSP-Woofer, 3" Soft-Dome Midrange, 1.1" Soft-Dome Tweeter
  - Frequency Response: 55 Hz – 25 kHz
  - Sensitivity: 91 dB
  - Continuous Power Handling: 200 Watts
  - System Impedance: 4 Ω



## Esotec System 362

The Esotec System 362 component systems combine one pair each of the MD 102 soft-dome tweeter, MD 142 soft-dome midrange, MW 172 woofers and the X 362 crossover networks into an incredibly refined and ultimately powerful three-way component system. All mounting hardware and grilles are included.

The Dynaudio Esotec mobile loudspeakers are perfectly complemented by the company's various dedicated crossover offerings. The Esotec component system crossovers are truly competition grade, using the highest quality components throughout. Custom produced, hand-selected, top quality polypropylene capacitors and custom wound, high-grade air-core inductors are utilized, as are impedance correction networks and tweeter protection circuits and independent tweeter adjustment levels for added system set-up flexibility. Mated to the advanced technology Esotec car series loudspeakers, the net result is a system that delivers authentic Dynaudio sound quality with a neutral tonal balance, incredible imaging and sound-staging capabilities, unsurpassed dynamics and complete transparency.



- Esotec System 362**
- Three-Way System
  - 8" MSP-Woofer, 3" Soft-Dome Midrange, 1.1" Soft-Dome Tweeter
  - Frequency Response: 40 Hz – 25 kHz
  - Sensitivity: 92 dB
  - Continuous Power Handling: 200 Watts
  - System Impedance: 4 Ω

