

Product Detail Page



SP-167E

Number: 10.3970

Series of $4\ \Omega$ hi-fi speakers for universal applications. Well manufactured and ideally suited e.g. as replacement speakers due to the exceptional price and their multi-purpose drive qualities.

Hi-fi bass-midrange speaker, $70\ W_{MAX}$, $35\ W_{RMS}$, $4\ \Omega$

- Great multi-purpose speaker
- Foam surround
- Replacement speaker for closed speaker systems and bass-reflex speaker systems



Technical Facts

Impedance (Z)	$4\ \Omega$
Resonant frequency (fs)	62 Hz
Max. frequency range	f3-6,000 Hz
Music power	$70\ W_{MAX}$
Power rating (P)	$35\ W_{RMS}$
SPL (1 W/m)	92 dB
Suspension compl. (Cms)	0.7 mm/N
Moving mass (Mms)	9.3 g
Mech. Q factor (Qms)	2.78
Electr. Q factor (Qes)	0.48
Total Q factor (Qts)	0.41
Equivalent volume (Vas)	17.88 l
DC resistance (Re)	$3.9\ \Omega$
Force factor (BxL)	5.43 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	25.5 mm
Voice coil former	aluminium
Linear excursion (XMAX)	$\pm 2.5\ \text{mm}$
Eff. cone area (Sd)	$135\ \text{cm}^2$



Magnet weight

570 g

Weight

1.15 kg

