

# Product Detail Page



## DT-28N

Number: 10.4020

**Neodymium hi-fi tweeter, 100 W<sub>MAX</sub>, 50 W<sub>RMS</sub>, 8 Ω**

- Outstanding sound characteristics
- Very linear reproduction even of lower frequencies
- High efficiency
- Extra efficient 28 mm silk cone
- Perfectly small front plate for high-performance speaker systems of the smallest size possible
- Mounting into perfect D'Appolito arrangements also in lying centres due to low magnetic dispersion



## Technical Facts

|                                     |                      |
|-------------------------------------|----------------------|
| <b>Impedance (Z)</b>                | 8 Ω                  |
| <b>Resonant frequency (fs)</b>      | 1,200 Hz             |
| <b>Max. frequency range</b>         | fx-20,000 Hz         |
| <b>Rec. crossover freq. (12 dB)</b> | 2,000 Hz             |
| <b>Music power</b>                  | 100 W <sub>MAX</sub> |
| <b>Power rating</b>                 | 50 W <sub>RMS</sub>  |
| <b>SPL (1 W/m)</b>                  | 94 dB                |
| <b>Voice coil diameter</b>          | 28 mm                |
| <b>Magnet diameter</b>              | 36 mm                |
| <b>Mounting cutout</b>              | Ø 46 mm              |
| <b>Mounting depth</b>               | 20 mm                |
| <b>Dimensions</b>                   | 55x55 mm             |
| <b>Weight</b>                       | 70 g                 |

