

Product Detail Page



SP-252E

Number: 10.3990

Series of $4\ \Omega$ hi-fi speakers for universal applications. Well manufactured and ideally suited e.g. as replacement speakers due to the exceptional price and their multi-purpose drive qualities.

Hi-fi bass-midrange speaker, $150\ W_{MAX}$, $75\ W_{RMS}$, $4\ \Omega$

- Multi-purpose speaker
- Foam surround
- Replacement speaker for closed speaker systems



Technical Facts

| | |
|-------------------------|--------------------|
| Impedance (Z) | $4\ \Omega$ |
| Resonant frequency (fs) | 42 Hz |
| Max. frequency range | f3-6,000 Hz |
| Music power | $150\ W_{MAX}$ |
| Power rating (P) | $75\ W_{RMS}$ |
| SPL (1 W/m) | 94 dB |
| Suspension compl. (Cms) | 0.33 mm/N |
| Moving mass (Mms) | 43 g |
| Mech. Q factor (Qms) | 3.13 |
| Electr. Q factor (Qes) | 0.60 |
| Total Q factor (Qts) | 0.50 |
| Equivalent volume (Vas) | 57 l |
| DC resistance (Re) | $3.75\ \Omega$ |
| Force factor (BxL) | 8.5 Tm |
| Voice coil induct. (Le) | 1.1 mH |
| Voice coil diameter | 35.5 mm |
| Voice coil former | aluminium |
| Linear excursion (XMAX) | $\pm 4\ \text{mm}$ |
| Eff. cone area (Sd) | $353\ \text{cm}^2$ |



Magnet weight

960 g

Weight

2.20 kg

