Product Detail Page







Hi-fi bass-midrange speaker, 80 $\mathrm{W_{MAX}},$ 50 $\mathrm{W_{RMS}},$ 8 $\,\Omega$

- Speakers of very high quality with extensive equipment
 Round aluminium diecast basket with recessed screw head holes
 Inverse rubber surround

- Triverse rubber surround
 Drilled pole core
 Excellent cone dampening
 Exceptionally deep bass reproduction for any bass and bass-midrange application





Technical Facts

Impedance (Z)	8 Ω
Resonant frequency (fs)	38 Hz
Max. frequency range	f3-5,000 Hz
Music power	80 W _{MAX}
Power rating (P)	50 W _{RMS}
SPL (1 W/m)	90 dB
Suspension compl. (Cms)	1.43 mm/N
Moving mass (Mms)	12.5 g
Mech. Q factor (Qms)	2.38
Electr. Q factor (Qes)	0.55
Total Q factor (Qts)	0.44
Equivalent volume (Vas)	37
DC resistance (Re)	6.2 ^{\Omega}
Force factor (BxL)	5.9 Tm
Voice coil induct. (Le)	0.45 mH
Voice coil diameter	25 mm
Voice coil former	aluminium
Linear excursion (XMAX)	±3mm
Eff. cone area (Sd)	137cm ²









Magnet weight	370 g	
Weight	1.32 kg	





