



# AIRMT-85

Order No.: 01.3190

**EUR 144,90** 

RRP\*

# **PRODUCTINFOS**

#### **Air Motion Transformers**

are a special type of tweeter systems which have been developed by the German physicist Oskar Heil during his research on the characteristics of the human ear. The main feature is a film-covered cone with a special folding which vibrates like an accordion when an audio signal is applied. This folding allows to accommodate a large cone area at a minimum of space. The AMTs feature a dynamic sound, an excellent transient response, a high efficiency and a low harmonic distortion.

### High-end Air Motion Transformer tweeter, 20 W, 4 $\Omega$

- Tweeter according to the Air Motion Transformer principle
- High-performance neodymium magnet system
- Fine, dynamic and brilliant reproduction of the high frequencies
- Folded cone made of Kapton and aluminium
- High efficiency
- For use from 2,500 Hz on
- Robust aluminium front panel



AIRMT-85 - Page: 2



### Klang+Ton 08,09/2016

"Compact AMT with quite a low crossover frequency possible for two-way speaker systems and multi-way speaker systems of highest quality."

# **TECHNICAL SPECIFICATIONS**

Impedance (Z)  $4 \Omega$ 

Operating voltage -

Frequency range 2,000-30,000 Hz

Resonant frequency (fs)

Rec. crossov. frequ. (fmax.)

(12 dB/oct.)

> 2,500 Hz

Power rating 20 W Peak music power output 40 W

Sensitivity 92 dB/W/m

Max. rated SPL -

Max. voltage -

Radiation angle, horizontal

Radiation angle, vertical

Suspension compl. (Cms) -

Moving mass (Mms) -

Mech. Q factor (Qms) -

Electr. Q factor (Qes) -

Total Q factor (Qts) -

Equivalent volume (Vas) -

DC resistance (Re)  $3.8 \Omega$ 

Force factor (BxL) Voice coil induct. (Le) -

Voice coil diameter -

Linear excursion (X<sub>MAX</sub>) -

Voice coil former

Eff. cone area (Sd) -

Magnet weight -

Magnet diameter neodymium rods

Mounting cutout Ø 66 mm

Mounting depth 35 mm

Mounting hole diameter Ø 75 mm



Hole spacing X-axis

Hole spacing Y-axis -

Dimensions Ø 85 mm x 36 mm

Outside diameter Ø 85 mm

Width 85 mm

Height 85 mm

Depth -

Protective class

Admiss. ambient temp.  $0-40 \, ^{\circ}\text{C}$  Weight  $0.288 \, \text{kg}$ 

Sales unit 1

Type of speaker

<sup>\*</sup> Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.