Product Detail Page





SP-302E Number: 10.4000

Series of 4 $\,\Omega\,$ Hi-fi Speakers for General Applications Neat workmanship and ideally suited e.g. as replacement speakers due to the exceptional price and their multi-purpose drive qualities.

Hi-fi bass-midrange speaker, 200 W_{MAX} , 100 W_{RMS} , 4 Ω





Technical Facts

Impedance (Z)	4 Ω
Resonant frequency (fs)	39 Hz
Max. frequency range	f3-5,500 Hz
Music power	200 W _{MAX}
Power rating (P)	100 W _{RMS}
SPL (1 W/m)	95 dB
Suspension compl. (Cms)	0.39 mm/N
Moving mass (Mms)	40 g
Mech. Q factor (Qms)	4.24
Electr. Q factor (Qes)	0.87
Total Q factor (Qts)	0.72
Equivalent volume (Vas)	141 I
DC resistance (Re)	3.6 Ω
Force factor (BxL)	6.63 Tm
Voice coil induct. (Le)	1.1 mH
Voice coil diameter	50 mm
Voice coil former	aluminium
Linear excursion (XMAX)	±4 mm
Eff. cone area (Sd)	518 cm ²









Magnet weight	960 g	
Weight	2.37 kg	





