MONACOR[®] INTERNATIONAL

Product Detail Page





Number: 10.3810

High-tech midrange speaker, 80 $W_{\text{MAX}},$ 40 $W_{\text{RMS}},$ 8 $\,\Omega$

- Solid aluminium cone and dustcap

- Special design for extra reinforcement
 Extra high cone stability ensures a maximum of fine dynamics
 As a single midrange speaker and particularly in D'Appolito arrangements, this speaker is of absolute high-end quality

17

| Technical Facts | |
|------------------------|--|
|------------------------|--|

| Impedance (Z) | | 8 Ω | |
|-------------------------|--------------|---------------------|--------------|
| Resonant frequency (fs) | | 80 Hz | |
| Max. frequency range | | fx-5,000 Hz | |
| Music power | | 80 W _{MAX} | |
| Power rating (P) | | 40 W _{RMS} | |
| SPL (1 W/m) | | 87 dB | |
| Suspension compl. (Cms) | | 0.79 mm/N | |
| Moving mass (Mms) | | 4.9 g | |
| Mech. Q factor (Qms) | | 3.05 | |
| Electr. Q factor (Qes) | | 0.67 | |
| Total Q factor (Qts) | | 0.55 | |
| Equivalent volume (Vas) | | 3.2 | |
| DC resistance (Re) | | 6.2 Ω | |
| Force factor (BxL) | | 4.81 Tm | |
| Voice coil induct. (Le) | | 0.3 mH | |
| Voice coil diameter | | 25 mm | |
| Voice coil former | | aluminium | |
| Linear excursion (XMAX) | | ±1.5 mm | |
| Eff. cone area (Sd) | | 55 cm ² | |
| MONACOR® | 🎟 Stage Line | | JT5 ° |

MONACOR, IMG Stage Line and CARPOWER are brands of the company group MONACOR INTERNATIONAL

| Magnet weight | 250 g |
|---------------|---------|
| Weight | 0.65 kg |

